



Piazza Borsellino e Falcone, 2 - 43039 Salsomaggiore Terme (PR)
 Tel. +39 0524/577889 - Fax. +39 0524/580796
 www.mediciautomazioni.it - info@mediciautomazioni.it
 REA N. 189702 - REG. IMPR. C.F. P.IVA 01950660348

TELECAMERA IP 2 MPX IR BULLET POE



SCHEDA TECNICA:

TELECAMERA	
CARATTERISTICHE	1/3" Progressive Scan CMOS AR0331
PIXELS	1920(H)x1080(V)
SCANNING SYSTEM	Progressive
ELECTRONIC SHUTTER SPEED	Auto/Manual, 1/3~1/10000s
ILLUMINAZIONE MINIMA	Color: 0. 1Lux, B/W: 0.005Lux ; 0Lux(IR on)
S/N RATIO	>50dB
CARATTERISTICHE	
MAX. IR LEDS LENGTH	Φ5 36pcs IR Led , IR Range 20m
DAY/NIGHT	Auto(ICR) / Color / B/W
BACKLIGHT COMPENSATION	BLC
WHITE BALANCE	Auto
GAIN CONTROL	Auto/Manuale
NOISE REDUCTION	2D
PRIVACY MASKING	N/A
LENTI	
FOCAL LENGTH	Vari-Focal,2.8-12mm
APERTURA MASSIMA	F1.6
ANGOLO DI VISUALE	89.9°-26.2°
MOUNT TYPE	MTV mount (Interchangeable Lens)
VIDEO	
COMPRESSIONE	H.264 / MJPEG
FRAME RATE	MAIN STREAM 1080P (1920*1080)25fps/HD 720P (1280*720) 25fps
	SUB STREAM D1 704*576 25FPS / CIF 25FPS
BIT RATE	32-8000 Kbps,Supports CBR/VBR
NETWORK	
ETHERNET	RJ-45 (10/100Base-T)

PROTOCOLLO	TCP/IP , UDP , RTP , RTSP , RTCP , HTTP , DNS , DDNS , DHCP , NTP , PPPOE , SMTP , UPNP
ONVIF	ONVIF Ver. 2.0
MAX. NUMERO DI UTENTI IN ACCESSO	10 users
SMART PHONE	iPhone, iPad, Android
General	
POWER SUPPLY	DC12V, PoE 802.3af (optional)
POWER CONSUMPTION	<6W
TEMPERATURA	-10°C~+60°C, 10%~90%
PROTEZIONE ESTERNA	IP66
DIMENSIONI	φ 60mm*160mm
PESO	0.90KG
DIMENSIONE PACCO	310mm*155mm*110mm
PESO PACCO	1.1KG
CERTIFICAZIONI	CE FCC RoHS